

# ETERNITY

GLAZED WALL TILE





Eternity 3x12 Glossy Subway - Ice  
CERT312ETYWHT



Eternity 3x12 Glossy Subway - Ash  
CERT312ETYSLV



Eternity 3x12 Glossy Subway - Smoke  
CERT312ETYGRY



Eternity 3x12 Glossy Subway - Black  
CERT312ETYBLK



3" x 12" Eternity  
Glossy Ceramic – White / Silver / Gray / Black

**PRODUCT SPECIFICATIONS**

| Product                           | SKU           | Actual Piece Size (inch) | Thickness (inch) | Weight (pound) | pcs/box | sf/box   | boxes/skid | sf/skid   |
|-----------------------------------|---------------|--------------------------|------------------|----------------|---------|----------|------------|-----------|
| Eternity 3x12 Glossy Subway Ice   | CERT312ETYWHT | 3" x 11.80"              | 0.31"            | 3.00 lb        | 44      | 10.82 sf | 72         | 779.04 sf |
| Eternity 3x12 Glossy Subway Ash   | CERT312ETYSLV | 3" x 11.80"              | 0.31"            | 3.00 lb        | 44      | 10.82 sf | 72         | 779.04 sf |
| Eternity 3x12 Glossy Subway Smoke | CERT312ETYGRY | 3" x 11.80"              | 0.31"            | 3.00 lb        | 44      | 10.82 sf | 72         | 779.04 sf |
| Eternity 3x12 Glossy Subway Black | CERT312ETYBLK | 3" x 11.80"              | 0.31"            | 3.00 lb        | 44      | 10.82 sf | 72         | 779.04 sf |

## TECHNICAL SPECIFICATIONS

| Technical Features       | Norms           | Requirement for Nominal Size N. |                    |
|--------------------------|-----------------|---------------------------------|--------------------|
|                          |                 | 7 cm ≤ N < 15 cm                | N ≥ 15 cm          |
| Length and Width         | EN ISO 10545-2  | ± 0.75 mm                       | ± 0.5%    ± 2.0 mm |
| Thickness                | EN ISO 10545-2  | ± 0.5 mm                        | ± 0.5%             |
| Straightness             | EN ISO 10545-2  | ± 0.5 mm                        | ± 0.5%    ± 1.5 mm |
| Squarness                | EN ISO 10545-2  | ± 0.75 mm                       | ± 0.6%    ± 2.0 mm |
| Surface Flatness         | EN ISO 10545-2  | ± 0.75 mm                       | ± 0.5%    ± 2.0 mm |
| Water Absorption         | ASTM C373       | E > 10%                         |                    |
| Modulus of Rupture       | EN ISO 10545-4  | ≥ 12 N/mm <sup>2</sup>          |                    |
| Thermal Shock Resistance | EN ISO 10545-9  | Required                        |                    |
| Chemical Resistance      | EN ISO 10545-13 | Indicated by manufacturer       |                    |
| Resistance to Stains     | EN ISO 10545-14 | Indicated by manufacturer       |                    |
| Shade Variation          | ANSI A137.1     | Indicated by manufacturer       |                    |

